

ICOM

IC-F3003 (VHF)
IC-F4003 (UHF)

tectel

WWW.TECTEL.CL

VHF AND UHF TRANSCEIVERS

5 W Output Power Also in UHF, 1500 mW Audio

Simple operation for instant communication

The IC-F3003 series is so easy to use there's no special training required. The few knobs and buttons are generously sized for easy operation and are designed to provide non-slip, positive action – even while wearing gloves.

Easy to hear in noisy areas

The radio provides 1500 mW* loud and clear audio with Icom custom high power handling capacity speaker. Clear communication is available even in noisy environments.

* Typical with internal speaker

Longer operating time

A new high efficiency FET of the IC-F3003 series reduces consumption current and provides up to 22 hours* of operating time with the BP-298, 2250 mAh (typical) supplied battery pack.

*TX: RX: Standby= 5: 5: 90. Power save function ON.

Weather resistant, dust protection, military rugged

While the radio is a compact unit with a height of only 111 mm, the radio is tested to dust protection and water resistant equivalent to IP54 and 11 categories of MIL-STD-810 environmental tests. In short, the IC-F3003 series is built rugged!

Internal VOX capability for hands-free operation

The radio has the internal VOX capability for hands-free operation. Optional compatible headset with plug adapter cable OPC-2004LA can be used with the radio. Also, the VOX gain and VOX delay time are adjustable.

Selective calling, quiet stand-by and more

2-Tone and 5-Tone signaling gives you selective calling, quiet stand-by and other convenient functions with programming. The radio "stun" function disables a radio over the air and the "revive" function restores the stunned radio.

Scan features

The priority scan allows you to monitor one or two priority channels while scanning other non-priority channels. The TX channel and talk back functions allow you to make a quick response while scanning.

Other features

- DTMF autodial
- CTCSS/DTCS encoder/decoder
- BIIS PTT ID transmission
- MDC PTT ID and emergency
- Low battery alert
- 2-step power save
- PC programmable
- Time out timer
- Talk around function
- Lone worker function
- Enhanced emergency
- 3-color LED
- Surveillance function



Dust Protection



Water Resistance



Limited functions.

SPECIFICATIONS

	IC-F3003	IC-F4003
GENERAL		
Frequency coverage	136–174 MHz	450–520 MHz 400–470 MHz
Number of channels	16 channels	
Type of emission	11K0F3E/16K0F3E	
Channel spacing	12.5/25 kHz	
Power supply requirement	7.2 V DC	
Current drain (approximate)		
TX High	1.3 A	1.6 A
RX Max. audio	500 mA (Internal SP)	500 mA (Internal SP)
Standby	75 mA	70 mA
Antenna impedance	50 Ω	
Operating temperature range	–30°C to +60°C, –22°F to +140°F (Radio only)	
Dimensions (W × H × D)	58 × 111 × 35.5 mm,	
(Projections not included)	2.3 × 4.4 × 1.4 mm (With BP-298)	
Weight (approximate)	265 g, 9.3 oz (With BP-298)	
TRANSMITTER		
Output power (at 7.2 V DC)	5 W, 2 W, 1 W (Hi, L2, L1)	
Max. frequency deviation	± 5.0 kHz/±2.5 kHz (Wide/Narrow)	
Frequency stability	±2.5 ppm	
Spurious emissions	70 dB minimum	
Residual modulations	58/53 dB typical (Wide/Narrow)	53/48 dB typical (Wide/Narrow)
Audio harmonic distortion (AF 1 kHz 40% deviation)	1.0%/1.5% typical (Wide/Narrow)	
Ext. microphone connector	3-conductor 2.5 (d) mm (1/10")/2.2 kΩ	
RECEIVER		
Sensitivity (at 12 dB SINAD)	0.25 μV typical	
Adjacent channel selectivity	78/70 dB typical (Wide/Narrow)	73/65 dB typical (Wide/Narrow)
Spurious response rejection	70 dB minimum	
Intermodulation rejection	75 dB typical	74 dB typical
Hum and noise (With CCITT filter)	54/50 dB typical (Wide/Narrow)	52/47 dB typical (Wide/Narrow)
Audio output power		
Internal SP (With 8 Ω load)	1500 mW typical (at 5% distortion)	
External SP (With 8 Ω load)	400 mW typical (at 5% distortion)	
Ext. speaker connector	2-conductor 3.5 (d) mm (1/8")/8 Ω	

Measurements made in accordance with TIA-603.

All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard

Dust & Water	IP54 (Dust-protection and water resistant)
--------------	--

OPTIONAL ACCESSORIES

Some accessories may not be available in some countries. Please ask your dealer for details.



Battery pack type	Capacity	Operating time*
BP-299	Li-ion	3050 mAh (min.) VHF 31.4 hrs.
		3150 mAh (typ.) UHF 29.4 hrs.
BP-298	Li-ion	2100 mAh (min.) VHF 22.4 hrs.
		2250 mAh (typ.) UHF 20.9 hrs.
BP-263	AA (LR6) × 6	—

* Tx: Rx: standby = 5:5:90. Power save function ON.


RAPID CHARGER



Charges the BP-298 in 3 hours and the BP-299 in 4.6 hours (approx.).

The BC-242 is supplied with the BC-240.

MULTI-CHARGER



* The AD-139 charger adapters are supplied with the BC-214N, depending on the charger version.


SPEAKER-MICROPHONES




CIGARETTE LIGHTER CABLE & POWER SUPPLY CABLES



HEADSETS



PTT SWITCH CABLE & PLUG ADAPTER CABLE



*2 Either the VS-4LA or OPC-2004LA is required for use with the HS-94, HS-95 or HS-97.

BELT CLIP



MB-124
Alligator type
Same as supplied.

STANDARD ANTENNAS

- FA-SC25V : 136–150 MHz
- FA-SC55V : 150–174 MHz
- FA-SC25U : 400–430 MHz
- FA-SC57U : 430–470 MHz
- FA-SC72U : 470–520 MHz

STUBBY ANTENNAS

- FA-SC56VS : 150–162 MHz
- FA-SC57VS : 160–174 MHz
- FA-SC73US : 450–490 MHz

CUT ANTENNAS

- FA-SC61VC : 136–174 MHz
- FA-SC61UC : 380–520 MHz

Supplied accessories:

- Battery pack, BP-298
- Desktop charger, BC-240
- AC adapter, BC-242
- Belt clip, MB-124
- Antenna

Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. All trademarks are the properties of their respective holders.



ANTONIO VARAS 894, PROVIDENCIA



(56-2) 2244 2264



WWW.TECTEL.CL



VENTA@TECTEL.L



WWW.TECTEL.CL